


SERIES TABLE 產品系列表

■ Chip Type Aluminum Electrolytic Capacitors 貼片式鋁電解電容器

Type 類型	Series 系列	Features 特性	Standard Type 標準型	Miniature 超小型	Low Impedance 低阻抗 抗電容	Long Life 長壽命	Operating Temperature Range(°C) 使用溫度範圍	Rate Voltage Range (V.D.C.) 額定工作電壓範圍	Capacitance Range(μ F) 靜電容量範圍	Load Life (Hours) 負荷壽命	Page 頁數		
Surface Mount Type 貼片式	General Purpose 普通型	CS	Standard size 標準品	●			-40 ~ +85	4 ~ 100	0.1 ~ 6800	2000	17		
		CK	Standard, wide temperature range 寬溫標準品	●			-40 ~ +105	4 ~ 100	0.1 ~ 6800	1000 ~ 2000	20		
	Low Leakage Current 低漏電型	SC	Low leakage current 低漏電品	●				-40 ~ +85	6.3 ~ 50	0.1 ~ 220	2000	23	
		Non-polarized 無極性型	CN	Bi-polarized 雙極性品	●				-40 ~ +85	6.3 ~ 50	0.1 ~ 100	1000	25
	KP		Bi-polarized, wide temperature range 雙極性寬溫品	●				-55 ~ +105	6.3 ~ 50	0.1 ~ 47	1000	27	
	Low Impedance 低阻抗型	LZ	Low impedance 低阻抗品			●			-55 ~ +105	6.3 ~ 35	1 ~ 4700	1000 ~ 2000	29
		KZ	Extra low impedance 極低阻抗品			●			-55 ~ +105	6.3 ~ 50	4.7 ~ 4700	1000 ~ 3000	32
	Long Life 長壽命型	FZ	Long life, extra low impedance 長壽命, 極低阻抗品			●	●		-55 ~ +105	6.3 ~ 100	3.3 ~ 4700	2000 ~ 5000	35
		EL	Long life assurance 寬溫長壽命品				●		-55 ~ +105	6.3 ~ 50	0.1 ~ 3300	2000 ~ 3000	38
		KL	5000 hours Load life 5000 小時長壽命品				●		-40 ~ +105	6.3 ~ 100	0.1 ~ 3300	3000 ~ 5000	40
	High Reliability 高可靠型	KH	High reliability 高可靠品				●		-40 ~ +125	10 ~ 450	3.3 ~ 2200	1000 ~ 5000	43
	High Voltage 高壓型	HU	Mid-to-high voltage 中高壓品				●		-40 ~ +105	160 ~ 450	3.3 ~ 47	5000	46

NOTE: All designs and specifications are for reference only and are subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.

注：以上所提供的設計及特性參數僅供參考作用，任何修改不作預先通知。如果在使用上有疑問，請在採購前與我們聯絡，以便提供技術上的協助。



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)

