2W005G THRU 2W10G

SILICON GLASS PASSIVATED BRIDGE RECTIFIERS Reverse Voltage - 50 to 1000 V

Forward Current - 2 A

Features

- Rating to 1000 V PRV
- · Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- · Glass passivated chip junction

Mechanical Data

• Case: WOM, Molded plastic • Polarity: As marked on Body

WOM


Dimensions in millimeters

Absolute Maximum Ratings and Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbols	2W005G	2W01G	2W02G	2W04G	2W06G	2W08G	2W10G	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Output Current at $T_A = 55$ °C	I _{F(AV)}	2							А
Peak Forward Surge Current, 8.3 ms Single Half- Sine-Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	50							А
Maximum Instantanous Forward Voltage at 1 A	V _F	1							V
Maximum Reverse Current $T_A = 25 ^{\circ}\text{C}$ at Rated DC Blocking Voltage $T_A = 100 ^{\circ}\text{C}$	I _R	10 1							μA mA
Operating and Storage Temperature Range	T _J , T _{stg}	- 55 to + 150							°C












Dated: 29/08/2008 B

FIG.1 - PEAK FORWARD SURGE CURRENT


PEAK FORWARD SURGE CURRENT,



NUMBER OF CYCLES AT 60Hz

FIG.2 - FORWARD DERATING CURVE OUTPUT RECTIFIED CURRENT


AVERAGE FORWARD OUTPUT CURRENT



AMBIENT TEMPERATURE, °C


FIG.3 - TYPICAL FORWARD CHARACTERISTIC





INSTANTANEOUS FORWARD VOLTAGE, VOLTS

FIG.4 - TYPICAL REVERSE CHARACTERISTIC



PERCENT OF RATED PEAK REVERSE VOLTAGE



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)







Dated: 29/08/2008 B