

# ST 78L24

## 3-Terminal positive voltage regulator

### Features

- Internal short-circuit current limiting
- Internal thermal overload protection
- Maximum output current of 100 mA ( $T_j = 25^\circ\text{C}$ )




1. Output 2. Common 3. Input  
TO-92 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Input Voltage	$V_{IN}$	40	V
Power Dissipation	$P_{tot}$	800	mW
Operating Temperature	$T_{opr}$	- 30 to + 75	°C
Storage Temperature Range	$T_{stg}$	- 55 to + 150	°C

### Electrical Characteristics (Unless otherwise specified, $V_{IN} = 33 \text{ V}$ , $I_{OUT} = 40 \text{ mA}$ , $C_{IN} = 0.33 \mu\text{F}$ , $C_{OUT} = 0.1 \mu\text{F}$ , $T_j = 25^\circ\text{C}$ )

Parameter	Symbol	Min.	Typ.	Max.	Unit
Output Voltage	$V_{OUT}$	23	24	25	V
Input Regulation $27.5 \text{ V} \leq V_{IN} \leq 38 \text{ V}$ $28 \text{ V} \leq V_{IN} \leq 38 \text{ V}$	Reg. line	-	35 30	350 300	mV
Load Regulation $1 \text{ mA} \leq I_{OUT} \leq 100 \text{ mA}$ $1 \text{ mA} \leq I_{OUT} \leq 40 \text{ mA}$	Reg. load	-	40 20	200 100	mV
Output Voltage $27.5 \text{ V} \leq V_{IN} \leq 38 \text{ V}$ $1 \text{ mA} \leq I_{OUT} \leq 40 \text{ mA}$	$V_{OUT}$	22.8	-	25.2	V
Output Voltage $V_{IN} = 33 \text{ V}$ $1 \text{ mA} \leq I_{OUT} \leq 70 \text{ mA}$	$V_{OUT}$	22.8	-	25.2	V
Quiescent Current	$I_B$	-	3.5	6.5	mA
Quiescent Current Change $28 \text{ V} \leq V_{IN} \leq 38 \text{ V}$ $1 \text{ mA} \leq I_{OUT} \leq 40 \text{ mA}$	$\Delta I_B$	-	-	1.5 0.1	mA
Output Noise Voltage at $T_a = 25^\circ\text{C}$ , $10 \text{ Hz} \leq f \leq 100 \text{ KHz}$	$V_{NO}$	-	200	-	µV
Ripple Rejection at $f = 120 \text{ Hz}$ , $29 \text{ V} \leq V_{IN} \leq 39 \text{ V}$ , $T_j = 25^\circ\text{C}$	RR	31	35	-	dB
Dropout Voltage at $T_j = 25^\circ\text{C}$	$ V_{IN}-V_{OUT} $	-	1.7	-	V
Average Temperature Coefficient of Output Voltage at $I_{OUT} = 5 \text{ mA}$	$TC_{VO}$	-	-2	-	mV/°C



**SEMTECH ELECTRONICS LTD.**  
Subsidiary of Sino-Tech International (BVI) Limited

