BC846P…BC850P

NPN Silicon Epitaxial Transistor

for switching and amplifier applications

As complementary types the PNP transistors BC856P...BC860P is recommended.





Bottom view
1. Base 2. Emitter 3. Collector
DFN1006-3H Plastic Package

Absolute Maximum Ratings (T_a = 25℃)

Parameter		Symbol	Value	Unit
Collector Base Voltage	BC846P	V_{CBO}	80	V
	BC847P, BC850P	V_{CBO}	50	V
	BC848P, BC849P	V_{CBO}	30	V
Collector Emitter Voltage	BC846P	V_{CEO}	65	V
	BC847P, BC850P	V_{CEO}	45	V
	BC848P, BC849P	V_{CEO}	30	V
Emitter Base Voltage	BC846P, BC847P	V_{EBO}	6	V
	BC848P,BC849P,BC850P	V_{EBO}	5	V
Collector Current		I_C	100	mA
Peak Collector Current		I_{CM}	200	mA
Power Dissipation		P_{tot}	250	mW
Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	- 65 to + 150	°C

Characteristics at T_a = 25℃

Parameter		Symbol	Min.	Typ.	Max.	Unit
DC Current Gain						
at V_{CE} = 5 V, I_C = 2 mA	Current Gain Group A	h_{FE}	110	-	220	-
	B	h_{FE}	200	-	450	-
	C	h_{FE}	420	-	800	-
Collector Base Cutoff Current						
at V_{CB} = 30 V		I_{CBO}	-	-	15	nA
Collector Emitter Saturation Voltage						
at I_C = 10 mA, I_B = 0.5 mA		V_{CEsat}	-	-	250	mV
at I_C = 100 mA, I_B = 5 mA		V_{CEsat}	-	-	600	mV
Base Emitter On Voltage						
at V_{CE} = 5 V, I_C = 2 mA		$V_{BE(on)}$	580	-	700	mV
at V_{CE} = 5 V, I_C = 10 mA		$V_{BE(on)}$	-	-	720	mV
Transition Frequency						
at V_{CE} = 5 V, I_C = 10 mA, f = 100 MHz		f_T	-	300	-	MHz
Output Capacitance						
at V_{CB} = 10 V, f = 1 MHz		C_{ob}	-	-	6	pF
Input Capacitance						
at V_{EB} = 0.5 V, f = 1 MHz		C_{ib}	-	9	-	pF

STATIC CHARACTERISTIC



BASE-EMITTER ON VOLTAGE



DC CURRENT GAIN



CURRENT GAIN BANDWIDTH PRODUCT



BASE-EMITTER SATURATION VOLTAGE
COLLECTOR-EMITTER SATURATION VOLTAGE



COLLECTOR OUTPUT CAPACITANCE