

# ST 2SC732

## NPN Silicon Epitaxial Planar Transistor

for switching and AF amplifier applications.

The transistor is subdivided into two groups, G and L, according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base  
TO-92 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	60	V
Collector Emitter Voltage	$V_{CEO}$	50	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current	$I_C$	150	mA
Base Current	$I_B$	30	mA
Power Dissipation	$P_{tot}$	400	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 55 to + 150	$^\circ\text{C}$

### Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 6 \text{ V}$ , $I_C = 2 \text{ mA}$	$h_{FE}$	200	-	400	-
	$h_{FE}$	350	-	700	-
Collector Base Cutoff Current at $V_{CB} = 60 \text{ V}$	$I_{CBO}$	-	-	100	nA
Emitter Base Cutoff Current at $V_{EB} = 5 \text{ V}$	$I_{EBO}$	-	-	100	nA
Collector Emitter Saturation Voltage at $I_C = 10 \text{ mA}$ , $I_B = 1 \text{ mA}$	$V_{CE(sat)}$	-	-	0.3	V
Gain Bandwidth Product at $V_{CE} = 6 \text{ V}$ , $I_C = 1 \text{ mA}$	$f_T$	-	150	-	MHz
Output Capacitance at $V_{CB} = 10 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{ob}$	-	2	-	pF



**SEMTECH ELECTRONICS LTD.**  
Subsidiary of Sino-Tech International (BVI) Limited

