

ST 2SC1393

NPN Silicon Epitaxial Planar Transistor TV VHF TUNER RF AMPLIFIER (FORWARD AGC)

The transistor is subdivided into three group, R, O and Y, according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base
TO-92 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	30	V
Collector Emitter Voltage	V_{CEO}	30	V
Emitter Base Voltage	V_{EBO}	4	V
Collector Current	I_C	20	mA
Collector Dissipation	P_{tot}	250	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 10 \text{ V}$, $I_C = 2 \text{ mA}$	h_{FE}	40	-	80	-
	h_{FE}	60	-	140	-
	h_{FE}	90	-	180	-
Collector Base Cutoff Current at $V_{CB} = 20 \text{ V}$	I_{CBO}	-	-	100	nA
Collector Base Breakdown Voltage at $I_C = 10 \mu\text{A}$	$V_{(BR)CBO}$	30	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 5 \text{ mA}$	$V_{(BR)CEO}$	30	-	-	V
Emitter Base Breakdown Voltage at $I_E = 10 \mu\text{A}$	$V_{(BR)EBO}$	4	-	-	V
Current Gain Bandwidth Product at $V_{CE} = 10 \text{ V}$, $I_C = 3 \text{ mA}$	f_T	-	700	-	MHz
Reverse Transfer Capacitance at $V_{CB} = 10 \text{ V}$, $f = 1 \text{ MHz}$	C_{re}	-	-	0.5	pF



SEMTECH ELECTRONICS LTD.
Subsidiary of Sino-Tech International (BVI) Limited

